CONTENTS:
Water-Based Fire Extinguishant
TRYLE Dispersion Mineral Platelets
Suspended in Water
Meets DOT Requirements
Normal Factory Charge: 2.0 gal. (8.7kg)
Gross Weight (with Hose): 30.0 lbs (13.6kg)
CAUTION!
Avoid contact with eyes, skin, and clothing.
May cause skin irritation upon prolonged or repeated contact. May cause slight irritation to eyes upon contact. May cause slight irritation to nose if ever in contact.
FIRST AID:
In case of contact, flush EYES with plenty of water. Wash SKIN with soap and water.
If irritation persists, consult a physician. Adverse health affects are not expected if SWALLOWED. Do not induce vomiting. Consult a physician if symptoms develop. If INHALED, get fresh air. If symptoms persist, consult a physician.
EfireX Incorporated
8975 Double Diamond Pkwy 13A
Reno, NV 89521
(775) 432-1009 www.efirex.com
ASSEMBLED IN THE U.S.A.
e-firex
Lithium Battery Fire Suppression Co.
INSTRUCTIONS
1
HOLD UPRIGHT. PULL RING PIN.
2
AIM AT THE BASE OF THE FIRE.
3
SQUEEZE LEVER. SWEEP FROM SIDE TO SIDE.
A
C
LITHIUM-ION BATTERY
ENCAPSULATOR
FIRE EXTINGUISHER
CLASSIFICATION 1-A
2.5 GAL. (9 LITER / 30 LB.)